

Advanced FPS with CSI:Ti technology:
 Higher sensitivity plus higher resolution
 Best image quality with lowest X-ray dose



HDR

Dental Digital X-ray Sensor HDR 500/600

Working Scheme:




APS CMOS technology:
 18.5µm pixel size
 5T pixel type
 Real resolution > 20 lp/mm.




Multi-user solution

The idea of <HandyDentist > management system is to provide multiuser solution. Sharing information in database. Plug and play connector make the sensor transferable from room to room.



New HandyDentist software:

Powerful image processing & preprocessing
 Easy to operate
 Multi-user solution
 Connectable to the most management systems on the market under DICOM3.0 protocol.



The Effect of image process
 "Optimizer" increase the intensity of contrast, make dentist feel easier to read the image.



TWAIN driver, which is compatible with the softwares of KODAK, SIRONA, SCHICK, etc.

Specification		
Item	HDR 500	HDR 600
Sensor		
Chip Type	CMOS APS	
Fiber Optical Plate	Yes	
Scintillator	GOS/CsI	
Dimension	27.5 x 38.5 mm	32.3 x 44.3 mm
Active Area	22.5 x 30 mm	27 x 36 mm
	675mm ²	972mm ²
Pixel size	18.5µm	
Image Pixel	1.9M(1600*1200)	2.7M(1920*1440)
Resolution (lp/mm)	Theoretical:27lp/mm Measured:12-14 lp/mm(GOS) 16-20 lp/mm(CsL)	
Operation	Windows 2000/XP/Vista/ Win7/Win8(32bit&64bit)	
Additional	TWAIN Driver	

HANDY(UK/SHANGHAI)TECHNOLOGIES CO., LTD

Tel: +86 021-56766108 Fax: +86 021-56766308
 Website: www.handydental.cn www.handycreate.com
 E-mail: h.sale@hotmail.com handy@handycreate.com
 After - sales supports:
 Skype: handysupports Email: support@handycreate.com